Acceleration Unit Converter and 0–100 km/h Time

Converts acceleration between m/s², g, ft/s², Gal (cm/s²), km/h per second and mph per second, with the time to reach 100 km/h at that constant acceleration.

Method: SI acceleration units and standard gravity

Input parameters

Unit system: SI

Parameter	Value	Unit
Acceleration	1.0000	g

Calculated results

Parameter	Value	Unit
In m/s²	9.8066	m/s²
In g	1.0000	g
In ft/s²	32.174	ft/s²
In Gal (cm/s²)	980.66	cm/s²
In km/h per second	35.304	km/(h·s)
Time from 0 to 100 km/h	2.8325	s

Notes for this case

• Standard gravity g_0 = 9.80665 m/s² (exact by definition); 1 ft/s² = 0.3048 m/s²; 1 Gal = 1 cm/s² (used in geophysics and earthquake engineering); 1 km/h per second = 0.2778 m/s². At constant acceleration, 0–100 km/h takes 27.78/a seconds; a typical family car averages about 0.25–0.3 g.

Formula and method

$$1\ g_0 = 9.80665\ \mathrm{m/s^2}, \quad 1\ \mathrm{Gal} = 0.01\ \mathrm{m/s^2}, \quad t_{0-100} = \frac{27.78\ \mathrm{m/s}}{a}$$

Variables

a	Acceleration	m/s²
t_{0-100}	Time from 0 to 100 km/h	s

Method and standards

Acceleration units.

Assumptions and limits

- Constant acceleration for the 0–100 time.

References

SI acceleration units and standard gravity

Report details

Report reference	FCC-GW0Y-VER8 (the same inputs always give the same reference)
Generated	23 November 2026, 18:01 UTC
Calculator	Acceleration Unit Converter and 0–100 km/h Time
Method last reviewed	17 November 2026
Software release	FireCAD Calc, release of 22 November 2026
Release checks	3 reference cases of this calculator, computed independently, are checked on every release

Results are for engineering estimation. Verify critical designs against the referenced standards and your own data.

This calculator online

https://calc.firecad.com/general/unit-conversions/acceleration-unit-converter

Open this case on calc.firecad.com →

Reopens the calculator with the inputs of this report.